

Declaration of Performance (DOP)

No. 9174 043 DOP 2019-07-02

1. Unique identification code of the product-type:

**Chimney systems with rigid or flexible inner liner and formed parts
made of polypropylene plastics acc. EN 14471:2013+A1:2015 type Jeremias-PP**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

**Chimney system with rigid or flexible plastic
inner pipes type Jeremias-PP¹⁾**

Model 1 ew-pp-starr	< DN200	T120 – H1 – W2 – O20 – LI – E – U
	≥ DN200	T120 – P1 – W2 – O20 – LI – E – U
Model 2 twin-p²⁾	< DN200	T120 – H1 – W2 – O00 – LE – E – U0
	≥ DN200	T120 – P1 – W2 – O00 – LE – E – U0
Model 2a) twin-p (V)³⁾	DN60 – 110	T120 – H1 – W2 – O00 – LE – E – U0
Model 2b) twin-p (Cu)⁴⁾	DN60 – 110	T120 – H1 – W2 – O00 – LE – E – U0
Model 3 twin-pl	< DN200	T120 – H1 – W2 – O00 – LI – E – U0
	≥ DN200	T120 – P1 – W2 – O00 – LI – E – U0
Model 4 ew-pps-flex	DN60 - ≤DN110	T120 – H1 – W2 – O00 – LI – E – U0
	> DN110 - DN160	T120 – P1 – W2 – O00 – LI – E – U0

¹⁾ Manufacturer product identification Jeremias-PP

²⁾ with stainless steel outer pipe, in highly polished finishing or painted

³⁾ with stainless steel Vision (reduced) outer pipe, in mat, brushed finishing

⁴⁾ with copper Vision (reduced) outer pipe

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Convey the products of combustion from heating appliances to the outside atmosphere

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Jeremias GmbH
Opfenrieder Straße 11-14
DE-91717 Wassertrüdingen
Tel.: +49 9832 68 68 0
Fax: +49 9832 68 68 68
Email: info@jeremias.de

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 2+ and System 3

7. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Notified factory production control certification body no. 0036 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity 0036 CPR 9174 043 of the factory production control.


8. Declared performance:

	Essential Characteristics	Performance	Harmonized technical specification
8.1	Compressive strength (max. installation height without intermediate support)	Sections and fittings: Model 1, 2, 2a), 3, 4: 30 m Model 2b): 15 m	EN 14471:2013+ A1:2015
8.2	Components subject to wind load (maximum spacing between lateral supports)	Model 1 ew-pp-starr DN (60 – 250): n.p.d. Model 2 twin-p DN (60 – 250): ≤ 2,4 m Model 2a) twin-p (V) DN (60 – 110): ≤ 2,0 m Model 2b) twin-p (Cu) DN (60 – 110): ≤ 2,2 m Model 3 twin-pl DN (60 – 110): n.p.d. Model 4 ew-pp-flex DN (60 – 160): n.p.d.	EN 14471:2013+ A1:2015
8.3	Components subject to wind load (free standing height above last support)	Model 1 ew-pp-starr DN (60 – 250): n.p.d. Model 2 twin-p DN (60 – 250): ≤ 4 m Model 2a) twin-p (V) DN (60 – 110): ≤ 4 m Model 2b) twin-p (Cu) DN (60 – 110): ≤ 3 m Model 3 twin-pl DN (60 – 110): n.p.d. Model 4 ew-pp-flex DN (60 – 160): n.p.d.	EN 14471:2013+ A1:2015
8.4	Fire prevention (Temperature level, distance from outer surface to combustible materials, class of outer wall)	Model 1 ew-pp-starr DN (60 – 250): T120 – O20 – E – U Model 2 twin-p DN (60 – 250): T120 – O00 – E – U0⁵⁾ Model 2a) twin-p (V) DN (60 – 110): T120 – O00 – E – U0⁵⁾ Model 2b) twin-p (Cu) DN (60 – 110): T120 – O00 – E – U0⁵⁾ Model 3 twin-pl DN (60 – 110): T120 – O00 – E – U0⁵⁾⁶⁾ Model 4 ew-pp-flex DN (60 – 160): T120 – O00 – E – U0⁶⁾ Installed in metal tubes ⁵⁾ or non-combustible duct ⁶⁾ with permanent ventilation. The distances do not apply for wall, ceiling or roof penetrations. Please consider the respective federal firing regulations (MFeuVo and FeuVo).	EN 14471:2013+ A1:2015
8.5	Gas tightness / leakage (Pressure level)	Model 1 ew-pp-starr DN (60 – <200): H1 Model 1 ew-pp-starr DN (≥200 – 250): P1 Model 2 twin-p DN (60 – <200): H1 Model 2 twin-p DN (≥200 – 250): P1 Model 2a) twin-p (V) DN (60 – 110): H1 Model 2b) twin-p (Cu) DN (60 – 110): H1 Model 3 twin-pl DN (60 – <200): H1 Model 3 twin-pl DN (≥200 – 250): P1 Model 4 ew-pp-flex DN (60 – ≤110): H1 Model 4 ew-pp-flex DN (>110 – 160): P1	EN 14471:2013+ A1:2015
8.6	Thermal performance (Temperature level)	Model 1 to 4: T 120	EN 14471:2013+ A1:2015
8.7	Dimensions in mm	Model 1 ew-pp-starr: 60; 80; 100; 110; 125; 160; 200; 250 Model 2 twin-p: 60/100; 80/125; 100/150; 110/160; 125/190; 160/230; 200/265; 250/315 Model 2a) twin-p (V) and 2b) twin-p (Cu): 60/100; 80/125; 100/150; 110/160 Model 3 twin-pl: 60/100; 80/125; 100/150; 110/160	EN 14471:2013+ A1:2015

8. Declared performance:

	Essential Characteristics	Performance	Harmonized technical specification
		Model 4 ew-pp-flex: 60; 80; 100; 110; 125; 160	
8.8	Thermal resistance m ² K/W	Model 1 to 4: R 00	EN 14471:2013+ A1:2015
8.9	Flow resistance of chimney sections (<i>r</i> = average roughness of inner liner)	Model 1 to 3: <i>r</i> = 1,0 mm Model 4: <i>r</i> = 3,0 mm	EN 13384-1
8.10	Flow resistance of chimney fittings (ζ = single resistance factor)	According to EN 13384-1	EN 13384-1
8.11	Flow resistance of terminals (ζ = single resistance factor in the exhaust system) (ζ = single resistance factor in the air supply)	Model 1 to 4: n.p.d.	EN 13384-1
8.12	Flexural tensile strength (real length of lateral displacement)	Model 1, 2, 2a), 3, 4: 1.500 mm Model 2b): n.p.d.	EN 14471:2013+ A1:2015
8.13	Flexural tensile strength (max. inclination)	Model 1 to 3: 87° Model 4: 0° - 45°	EN 14471:2013+ A1:2015
8.14	Resistance against chemicals (Condensate resistance)	Model 1 to 4: W	EN 14471:2013+ A1:2015
8.15	Resistance against chemicals (Corrosion resistance)	Model 1 to 4: 2	EN 14471:2013+ A1:2015
8.16	UV-resistance (installation class)	Model 1; 3 and 4: LI Model 2: LE	EN 14471:2013+ A1:2015
8.17	Thermal resistance	Model 1 to 4: T120 Also suitable for block heating stations if an exhaust gas temperature limiter with an acting point of max. 110° C is integrated. The exhaust gas temperature should not exceed 100°C during continuous operation.	EN 14471:2013+ A1:2015
8.18	Fire behaviour	Model 1 to 4: E	EN 14471:2013+ A1:2015
8.19	Freeze-thaw resistance	Model 1 to 4: Yes	EN 14471:2013+ A1:2015
8.20	Dangerous substances	No release of dangerous substances in planned operation	

8. Declared performance:

	Other Characteristics	Performance	Harmonized technical specification
	Characteristics for the wind direction of terminals	Model 1 to 4: n.p.d.	EN 14471:2013+ A1:2015
	Resistance of terminals to rainwater penetration	Model 1 to 4: n.p.d.	EN 14471:2013+ A1:2015
	Resistance of terminals to icing	Model 1 to 4: n.p.d.	EN 14471:2013+ A1:2015
<p>9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.</p> <p>Signed for and on behalf of the manufacturer by:</p> <p>Wassertrüdingen, 02nd July 2019</p> <div style="text-align: right;">  Stefan Engelhardt CEO </div>			

Product information

“Chimneys – System chimneys with plastic flue liners – requirements and test methods” EN 14471

Manufacturer's identification:

Jeremias GmbH
Opfenrieder Str. 11-14
91717 Wassertrüdingen
 Tel.: +49 (0) 9832 / 68 68-50
 Fax: +49 (0) 9832 / 68 68-68
 Internet: www.jeremias.de
 E-Mail: info@jeremias.de

Product trade name:

Jeremias-PP (chimney system made of polypropylene)
 Product subcategory: **ew-pp-starr / twin-p / twin-p (V) / twin-p (Cu) / twin-pl / ew-pp-flex**

Certification office:

TÜV SÜD Industrie Service GmbH

Name and position of the responsible person:

Stefan Engelhardt CEO

Identification of accompanying documents

0.1 ew-pp-starr	EN 14471	T120 T120	H1 P1	W W	2 2	O20 O20	LI LI	E E	U U	< DN200 ≥ DN200	Single wall chimney system made of plastic, applicable for moisture resistant operation mode in positive pressure up to max. 5000Pa, ventilated throughout the whole length, for the installation inside buildings as indoor air independent connection piping or for the installation in non-combustible ductworks, that comply with the national fire protection regulations, in indoor air dependent / independent operation mode
0.2 twin-p	EN 14471	T120 T120	H1 P1	W W	2 2	O00 O00	LE LE	E E	U0 U0	< DN200 ≥ DN200	Multiple wall chimney system, inner pipe made of plastic with annular gap for ventilation, outer tube made of stainless steel, applicable for moisture resistant, indoor air dependent / independent operation mode in positive pressure up to max. 5000Pa. Installation outside / inside buildings or installation in non-combustible ductworks, that comply with the national fire protection regulations.
0.2a) twin-pv	EN 14471	T120	H1	W	2	O00	LE	E	U0	DN60 – 110	Multiple wall chimney system, inner pipe made of plastic with annular gap for ventilation, reduced outer tube made of stainless steel, applicable for moisture resistant, indoor air dependent / independent operation mode in positive pressure up to max. 5000Pa., locking band required. Installation outside / inside buildings or installation in non-combustible ductworks, that comply with the national fire protection regulations.
0.2b) twin-pv-cu	EN 14471	T120	H1	W	2	O00	LE	E	U0	DN60 – 110	Multiple wall chimney system, inner pipe made of plastic with annular gap for ventilation, reduced outer tube made of copper, applicable for moisture resistant, indoor air dependent / independent operation mode in positive pressure up to max. 5000Pa. Locking band required. Installation outside / inside buildings or installation in non-combustible ductworks, that comply with the national fire protection regulations.
0.3 twin-pl	EN 14471	T120 T120	H1 P1	W W	2 2	O00 O00	LI LI	E E	U0 ¹⁾ U0 ¹⁾	< DN200 ≥ DN200	Multiple wall chimney system, inner pipe made of plastic with annular gap for ventilation, outer pipe made of galvanized and powder coated sheet metal, applicable for moisture, indoor air dependent / independent operation mode in positive pressure up to max. 5000Pa. ¹⁾ Installation inside buildings as connection piping.
0.4 ew-pp-flex	EN 14471	T120 T120	H1 P1	W W	2 2	O00 O00	LI LI	E E	U0 U0	DN60- ≤DN110 >DN110-DN160	Single wall chimney system, consisting of rigid and flexible plastic pipes, applicable for moisture resistant, indoor air dependent / independent operation mode in positive pressure up to max. 5000Pa, ventilated throughout the whole length, for installation in non-combustible ductworks, that comply with the national fire protection regulations.

Product description	
Standard number	EN 14471
Temperature level	T120
Pressure level	O20
Condensate resistance (W: wet / D: dry)	LI
Corrosion resistance	LI
Distance to combustible materials	LI
Installation location: (LI: inside building, LE: inside & outside of buildings)	LI
Fire behavior	E
outer casings	U0
Diameter (Ø) in mm	DN60- ≤DN110 / >DN110-DN160

EN 14471

Compressive strength: maximum load 30 m without intermediate support
 maximum load 15 m without intermediate support (Model 2b)

Wind stress:

ew-pp-starr: n.p.d
twin-p: 4 m between two wall fixations, 2,4 m free standing
twin-p (V): 4 m between two wall fixations 2,0 m free standing with locking band
twin-p (Cu): 3 m between two wall fixations 2,2 m free standing with locking band
twin-pl: ¹⁾ Installation only inside buildings, as connection piping towards vertical chimney, max. 3 m between two wall fixations
ew-pp-flex: n.p.d

Nominal diameters (Ø) inner pipes / outer pipes in mm:

ew-pp-starr: 60; 80; 100; 110; 125; 160; 200; 250
twin-p: 60/100; 80/125; 100/150; 110/160; 125/190; 160/230; 200/265; 250/315
twin-p (V) / twin-p (Cu): 60/100; 80/125; 100/150; 110/160
twin-pl: 60/100; 80/125; 100/150; 110/160
ew-pp-flex: 60; 80; 100; 110; 125; 160

Thermal resistance: 0 m²K/W

Flow resistance: average roughness acc. EN 13384-1

Bending tensile strength: Non-vertical installation between two supports:

ew-pp-starr: ≤ 2 m; **twin-p:** 4 m; **twin-p (V):** 4 m; **twin-p (Cu):** n.p.d.; **twin-pl:** 4 m;
ew-pp-flex: not possible

Condensate resistance: given

Resistance against thermic exposure: T120

Reaction to fire acc. EN 13501-1: E

Raw material designation: pp = polypropylene

Recycling:  EN ISO 14021

¹⁾ Acc. DIN V 18160-1 components of chimney systems may also be used as connection pieces