

Declaration of Performance (DOP)

No. 9174 017 DOP 2019-11-27

1. Unique identification code of the product-type:

Single wall connecting pipe type FERRO-LUX according to EN 1856-2:2009

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

Rigid, single wall connecting pipe type FERRO-LUX ¹⁾

Model 1	DN (115)	T600 – N1 – D – Vm – L01200 – G375NM ²⁾
	DN (120)	T600 – N1 – D – Vm – L01200 – G375NM ²⁾
	DN (130)	T600 – N1 – D – Vm – L01200 – G390NM ²⁾
	DN (150)	T600 – N1 – D – Vm – L01200 – G450NM ²⁾ (with radiation protection G400)
	DN (160)	T600 – N1 – D – Vm – L01200 – G480NM ²⁾ (with radiation protection G400)
	DN (180)	T600 – N1 – D – Vm – L01200 – G540NM ²⁾ (with radiation protection G400)
	DN (200)	T600 – N1 – D – Vm – L01200 – G600NM ²⁾ (with radiation protection G400)
	DN (250)	T600 – N1 – D – Vm – L01200 – G750NM ²⁾ (with radiation protection G400)

¹⁾ Manufacturer product identification

²⁾ Not Measured (NM) means 3 times the Nominal Diameter with a minimum of 375 mm

³⁾ Measured (M)

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Convey the products of combustion from heating appliances to the chimney

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Jeremias GmbH
Opfenrieder Straße 11-14
DE-91717 Wassertrüdingen
Tel.: +49 9832 68 68 0
Fax: +49 9832 68 68 68
Email: info@jeremias.de

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 2+

7. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Notified factory production control certification body no. 0036 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity 0036 CPR 9174 017 of the factory production control.


8. Declared performance:

	Essential Characteristics	Performance	Harmonized technical specification
8.1	Compressive strength	Model 1 DN (115- 250): n.p.d.	EN 1856-2:2009
8.2	Tensile strength	Model 1 DN (115- 250): n.p.d.	
8.3	Non vertical installation	Model 1 DN (115- 250): Horizontal 2,5 m between two supports or fixations	
8.4	Resistance to fire	(Resistance to fire from inside to outside) Model 1 DN (115): G375 NM Model 1 DN (120): G375 NM Model 1 DN (130): G390 NM Model 1 DN (150): G450 NM (with radiation protection distance: 400 mm) Model 1 DN (160): G480 NM (with radiation protection distance: 400 mm) Model 1 DN (180): G540 NM (with radiation protection distance: 400 mm) Model 1 DN (200): G600 NM (with radiation protection distance: 400 mm) Model 1 DN (250): G750 NM (with radiation protection distance: 400 mm)	EN 1856-2:2009
8.5	Gas tightness/ leakage	Model 1 DN (115- 250): N1	EN 1856-2:2009
8.6	Flow resistance of chimney sections and fittings	According to EN 13384-1	EN 1856-2:2009
8.7	Sootfire resistance	Model 1 DN (115- 250): Yes ²⁾ ²⁾ because designated G	EN 1856-2:2009
8.8	Thermal performance under normal operating conditions	Model 1 DN (115- 250): T600* *(Heating strain at nominal operating temperature)	
8.9	Durability: Water and vapour diffusion resistance	Model 1 DN (115- 250): No	EN 1856-2:2009
8.10	Condensate penetration resistance	Model 1 DN (115- 250): No	
8.11	Against corrosion	Model 1 DN (115- 250): Vm	
8.12	Freeze thaw resistance	Model 1 DN (115- 250): Yes	

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Wassertrüdingen, 27th November 2019



.....
Stefan Engelhardt CEO

Product information

“Chimneys - Requirements for metal chimneys - Part 2:
Metal flue liners and connecting flue pipes” EN 1856-2:2009

Manufacturer’s identification:

jeremias GmbH
Opfenrieder Str. 11-14
91717 Wassertrüdingen
Tel.: +49 (0) 9832 / 68 68-50
Fax: +49 (0) 9832 / 68 68-68
Internet: www.jeremias.de
E-Mail: info@jeremias.de

Product trade name:

FERRO-LUX (Single wall rigid connections)

Certification office:

TÜV SÜD Industrie Service GmbH

Name and position of the responsible person:

Stefan Engelhardt CEO

Identification of accompanying documentation

Rigid connections	EN 1856-2	T600	N1	D	Vm-L01200	G375 NM	115	Single wall connections, soot fire resistant, for connections of stoves / boilers for chimneys / flue systems, ventilated throughout the whole length.
						G375 NM	120	
						G390 NM	130	
						G450 NM¹	150	
						G480 NM¹	160	
						G540 NM¹	180	
						G600 NM¹	200	
					G750 NM¹	250		

Product description								Properties of a rigid metallic connection
Standard number								<u>Compressive strength:</u> n.p.d.
Temperature level								<u>Flexural strength:</u> n.p.d.
Pressure range level								<u>Flow resistance:</u> Average roughness: 1,0 mm, Zeta-values according to EN 13384-1
Condensate resistance (W: wet / D: dry)								<u>Thermal resistance:</u> 0 m ² K/W
Corrosion resistance								<u>Soot fire resistance:</u> Yes
Flue liner material specification								<u>Freeze-thaw resistance:</u> Yes
Sootfire resistance and distance (in mm) to combustible material without radiation protection								
Nominal diameter (Ø) in mm								

¹ With radiation protection, the distance to combustible materials can be established for all the Ø at 400mm.